## Puropack® PPA510Plus

Macroporous Type II Strong Base Anion Exchange Resin

PRODUCT DATA SHEET

Puropack PPA510Plus is a specially produced, premium narrow size grading, macroporous type 2 strong base anion exchange resin with a particle size grading that is ideal for use in packed bed systems. Its macroporous structure offers excellent resistance to osmotic and physical shock.

Puropack PPA510Plus has a high operating capacity, especially on high-FMA feedwaters, as well as a high reversible sorptive capacity for complex organic materials, such as the fulvic and humic acids which occur in many surface water supplies. It is one of a range of Puropack products manufactured for use in modern day water treatment applications. Puropack PPA510Plus is especially recommended for use in all counterflow demineralization systems, including the Puropack packed bed ystem. It has a specially tailored size grading which provides for economical regeneration by counterflow techniques. Puropack is a maximum performance packed bed system which provides a combination of superior engineering principles and improved resins that together optimize water treatment plant performance. For more information please refer to the Puropack Manual or your local Purolite Sales Office.

## **Typical Physical and Chemical Characteristics**

Application	Demineralization with High Regeneration Efficiency - Uniformly Sized Packed Bed Grading
Polymer Structure	Macroporous polystyrene crosslinked with divinylbenzene
Appearance	Spherical beads
Functional Group	Type II Quaternary Ammonium
Ionic Form as Shipped	CI
Total Capacity (min.)	1.15 eq/l (25.1 Kgr/ft <sup>3</sup> ) (Cl <sup>-</sup> form)
Moisture Retention	48 - 56 % (Cl <sup>-</sup> form)
Mean Size Typical	750 ± 100 µm
Uniformity Coefficient (max.)	1.2 - 1.4
Reversible Swelling, $Cl^{-} \rightarrow OH^{-}$ (max.)	15 %
Specific Gravity	1.08
Shipping Weight (approx.)	680 - 710 g/l (42.5 - 44.4 lb/ft <sup>3</sup> )
Temp Limit, Cl <sup>-</sup> Form	100°C (212°F)
Temp Limit, OH <sup>-</sup> Form	35°C (95°F)



Americas T +1 610.668.9090 F +1 484.384.2751 americas@purolite.com Europe T +44 1443 229334 F +44 1443 227073 europe@purolite.com Asia Pacific T +86 571 876 31382 F +86 571 876 31385 asiapacific@purolite.com